

DAHLE Paper SAFE® 140 (23140)

Space-saving document shredder for small offices and home offices


DAHLE Paper SAFE® 140

Description

- Compact document shredder for small offices and home offices
- oil- and maintenance free operation
- Convenient feed and reverse function for manual control
- 2-year warranty on proper working order provided the product is used as intended.
- Visual overload indicator
- Practical filling-level indicator through viewing window
- Removable top part
- Extra small particles for optimum utilization of volume
- Integrated light barrier for automatic start and stop
- Automatic motor cut-out
- Overheating protection with overheating display.
- Angled cold device cable
- Dimensions (H x W x D): 366 x 347 x 217 mm



Product details




Entry width 220 mm



Removable top part for conveniently emptying the waste box



Deskside document shredders: performance and convenience directly at the desk



Waste collection volume 12 liters



Cross cut



Comfortable and environmentally friendly shredding - no time - consuming lubrication of the cutting cylinders required



DAHLE Paper SAFE® 140

Technical data

• Product name	: DAHLE Paper SAFE® 140
• Entry width in mm	: 220 mm
• Sheet capacity (80g/sqm)*	: 0 - 10 sheets
• Shred Type	: Cross Cut
• Particle size (in mm)	: 5 x 18 mm
• Security levels	: P-4/F-1/T-4/E-3
• Run time	: 20 min
• Speed (m/min)	: 3.5 m/min
• Shred Cards	: Yes
• Shred Paper clips	: Yes
• Waste collection volume (in l)	: 12 l
• Noise level when idle (db)	: 65 dB(A)
• Power consumption	: 220 W
• Power supply	: 230 V
• Period Of Warranty	: 1 Year
• Weight net	: 4.8 kg
• Article number	: 23140-16170
• Dimensions (H x W x D)	: 366 x 347 x 217 mm

* Maximum number of sheets which can be cut in a single pass under the following conditions: New cutting cylinders (oiled if necessary), cold motor, power supply with nominal voltage and nominal frequency (230V/50Hz; 120V/60Hz). Non-conformances can lead to a lower sheet capacity and increased running noise. Sheets are fed at 90° either portrait or landscape. The sheet capacity may vary depending on paper properties and feed.

